


POOL/SPA PERMIT REQUIREMENTS

7550 Sunwood Drive NW
Ramsey, Minnesota 55303
City Hall: 763-427-1410
Building and Inspections: 763-433-9850
Fax: 763-433-9848
www.cityoframsey.com/permits
permits@cityoframsey.com



This pamphlet is a compilation of some of the standard requirements based on the State Building Code and City Zoning Code for projects of this type. This information packet does not contain all of the specific codes for construction and should only be used as a guide. The permittee is responsible to meet all code requirements applicable to each project.

Pool/Spa Definitions

A swimming pool is defined as any pool, permanent or portable, above or below ground, and which is more than 24 inches in depth and has a surface area which exceeds 200 square feet (equivalent of 16 foot diameter).

A spa is defined as a unit primarily designed for therapeutic and/or recreational use, which is not drained, cleaned or refilled for each individual. It may include, but not be limited to: hydro-jet circulation, hot water, cold water, mineral baths, air induction bubbles or any combination thereof. Industry terminology for a spa includes, but it not limited to: therapeutic pool, hydrotherapy pool, whirlpool, hot spa, and hot tub.

Required Permits

Swimming pools which exceed both 5,000 gallons in capacity and a 24" depth shall require a building permit. Pools or spas less than 5,000 gallons do not require a building permit; however; will require a zoning permit prior to being constructed or installed.

The permit application shall be submitted with a site plan showing the proposed location on the lot along with location and proximity of other buildings and structures, lot lines and septic system (if applicable). Also needed are the pool drawings or specifications.

Construction Requirements

Precaution shall be taken during construction to avoid damage, hazard or inconvenience to adjacent or nearby properties, and to assure that proper care is taken in stock piling excavated material in order to avoid erosion, dust, or other infringements onto adjacent property. During construction of any in-ground pool or spa, the construction area must be secured with a portable fence which is not less than 4 feet in height.

Setback Requirements

Swimming pools and spas shall be setback a minimum of 10 feet from all adjoining lots. For corner lots, swimming pools and spas shall meet the required side yard setback for buildings in the applicable zoning district.

Pools and spas shall not be located closer than 4 feet to the principal structure, within 10 feet of the edge of septic tank(s) and 20 feet of the edge of the drainfield. Pools and spas cannot be located any closer than 3' from a private well. All heating and filtering equipment shall be located at least 30 feet from the inhabited portion of neighboring residences.

No pool/spa walkway, patio, decking, or any other portion of a pool/spa shall be located in an easement or setback of any kind.

Fence Requirements

Above ground pools that have a minimum side-wall height of 4 feet do not need to be fenced, but shall have removable steps which are not in place when the pool is unattended.

An above ground pool with less than 4 foot sidewalls shall be fenced as would an in-ground pool.

An in-ground pool, or the yard in which it is located, must be surrounded by a non-climbing type fence (with no external handholds or footholds) at least 4 feet high.

All fence openings shall be equipped with self-closing, self-latching devices that are lockable.


Required Inspections

A footing inspection is required for in-ground pools after the excavation, temporary fence installation and forms and/or reinforcing is supported in place. For above ground pools, a site inspection is required after the location has been staked. Plumbing and mechanical inspections shall be required as applicable for the scope of work being performed prior to concealing or covering work. Electrical permits and inspections as required by the Minnesota State Electrical Code. A final inspection is required after all the work is completed.

Miscellaneous

A backflow prevention device must be provided on the water faucet used for filling the pool or spa. Provide an anti-vortex main drain for all pools. Tempered glass is required when the pool/spa is located within five feet of glass and the glazing is 60 inches or less in height from the walking surface.

Discuss your proposed pool, or spa, addition with your insurance provider and homeowner's association (if applicable). They may have additional regulations.



Swimming Pool Guidelines